

Wave Soldering System



ATF 13/25

Lead-free ready



System:

- Lead-free ready
- Stainless steel foam fluxer
- IR-preheater, with Ceran glass cover
- Dual wave, with direct driven solder pumps
- Wave intermittent operation
- Belt-driven pallet conveyor
- Microprocessor controlled
- Meets VDE safety regulations

Options:

- Pumpless spray fluxer
- Integrated filter above spray fluxer
- Convection preheater
- Tunnel above preheater
- Nitrogen inerting
- Pin code reader
- Interchangeable solder pot
- Bench, with or without panels and doors
- PC-software
- PC-version
- Assembly conveyor systems

Description Wave Soldering System ATF 13/25



System

- Sturdy steel base frame
- All modules designed for easy maintenance


- Rigid hoods include antistatic safety glass allow full monitoring of working process
- 2 exhaust ducts (above fluxer and solder pot)
- Bench, with or without panels and doors



Fluxer module

- Foam fluxer fitted as standard
- Whole unit is adjustable in height
- Air regulator pressure gauge and flow control valve


- Spray fluxer
- Programmable flux quantity



Preheat module

- High efficiency IR preheater
- Fine adjustment of temperature
- Ceran glass cover for easy cleaning

- All values shown at digital display
- Convection



Solder pot ready for Lead-free

- Combination of ceramic coating (solder pot, flow ducts and pumps) and chemical-thermal treatment of nozzles.
- Quick-lock solder pumps
- Direct driven pumps (24V DC motors)


- Removable flow ducts and nozzles
- Solder temperature shown at digital display
- Interchangeable solder pot



Solder wave

- Special designed flow ducts to reduce dross formation
- Separate Microprocessor controlled wave heights

- Dual wave as standard (Lambda and chip nozzle)
- Wave intermittent operation



Conveyor

- Belt driven conveyor
- 24V DC drive motor
- Conveyor speed 0 – 2 m/min.

- 1 PCB carrier included
- Adjustable conveyor angle 5-9°
- Conveyor speed shown at digital display



Controller

- Microprocessor controller (with a 2-line display)
- User friendly operation, multi langual
- Solder pot on/off timer
- Memory of 99 recipes

- Pin Code reader
- PC-software



PC-option

- For profile management
- For process documentation the relevant data are recorded, with password protection
- Incl. LAN network connection
- Incl. flat screen monitor

- standard
- optional

Distributed via:

ATF GmbH

Bildstraße 27
 D-97903 Collenberg
 Tel: + 49 9376 9711 0
 Fax: + 49 9376 9711 29
 e-mail: info@atf-collenberg.de
 www.atf-collenberg.de